



Art. No.: 01495

Universal busbar support, 3-pole

60 mm system up to 630 A

For 12 x 5 mm to 30 x 10 mm busbars

Latching mechanism for adaptation to respective busbar size

Product Group : 6

Subgroup : 09

Standards :

IEC / EN 60439-1

Approvals :

Germanischer Lloyd, GOST, CSA, UL

Type No.: S610

Duty Tariff No.: 8546 90 10

UL File Number: E123577, Category: NMTR2, www.ul.com

CSA File Number: 110285, Class Number: 3211-37, <http://directories.csa-international.org>

The product must not be CCC certified

Electrical Data :

3-pole busbar system, 690 V

max. 630 A rated current

Short-circuit withstand capability:

surge withstand strength > 30 kA at a

busbar support spacing of 550 mm

surge withstand strength > 50 kA at a

busbar support spacing of 250 mm

see short-circuit withstand capability diagram for further details

Mechanical Data :

Width x Height x Depth (mm): 20 x 191 x 50
Weight (kg/100): 12,7
screw tightening torque: 4 Nm

Remarks :

Also with interior screw-in holes useable as centre support

Pack Size : 10

Catalog 2006 :

Page: 2/1

Accessories to Article 01495 :



01573 end cover
for busbar support 01 495 and 01 500